



**A spader for heavy tilling
Specially designed for depths
of up to 47.24 inches (120 cm).**



**For the really heavy tilling jobs: Farmax KRG.
The KRG is Farmax's strongest spader, specially
designed for depths of up to 47.24 inches (120 cm).**

Thanks to the special blades the KRG produces an even tilth. The Farmax KRG has operating widths of 98.43" (250 cm) and 110.24" (280 cm), and is equipped as standard with two adjustable guide shoes for depth.

Multifunctional tyre roller

The KRG is supplied as standard with a roller consisting of four tyres. This tyre roller ensures that the soil is pressed properly after rotavation to restore the groundwater system and ensure that excess rainwater drains away quickly. This prevents the soil drying out.



Drive to main axle (rotor): double sprocket wheel transmission in an oil sump, driven by a heavy-duty transmission case with differential.

Capacity: Up to 0,74 acres (0.3 hectare) per hour in optimum conditions

Power take-off revs: 1000 r.p.m.

Advantages

- tills soil to depth of up to 47.24 inches (120 cm)
- special spader blades make for even tilth
- low maintenance and very user-friendly
- tyre roller ensures consistent rotavation depth and better groundwater management, and makes for easy transport

Thanks to the tyre roller, the machine is easy to transport. This reduces the load on the tractor, both on and off the road. The roller also ensures that the machine continues to work at a constant depth. The KRG is unique as a drawn spader.



Specially designed spader blades



Tyre roller ensures better groundwater management



Option: Oil cooler to cool oil in transmission case



Extra-heavy drive chain

Technical Data



type	operating width	max. operating depth	standard weight	required power kW/HP	number of spades
KRG 250	98.43" - 250 cm	47.24" - 120 cm	11,243 Lbs - 5.100 kg	140/190	24
KRG 280	110.24" - 280 cm	47.24" - 120 cm	11,541 Lbs - 5.235 kg	177/240	24

SALE ORGANIZATION

Wasse BV
Oranjekanaal Zuidzijde 17
9415 PR Hijken (NL)
Tel: +31 (0)593-524066
Gerry Wasse: +31 (0)6-53428536
sales@farmaxspadingmachine.com

MANUFACTURER

Farmax metaaltechniek BV
Nijverheidsstraat 5
7591 BM Denekamp (NL)
Tel: +31 (0)541-351267
www.farmax.info

FOLLOW US  

YOUR DEALER